Design Standards

August 24, 2007

FIRECLAY TOD

FIRECLAY TOD DESIGN STANDARDS

The following Design Standards have been established in order to create a consistent visual theme throughout the Murray Fireclay TOD/Redevelopment Area. The standards have been divided into three primary sections: Streetscape, Landscape, and Monumentation. Each section contains standards that must be followed within the Fireclay TOD, and recommendations which provided examples:

1) STREETSCAPE

	DESIGN STANDARDS Tree Grates Tree Guards Trash Receptacles Bollards Benches Planters Light Fixtures. Bicycle Racks Paving	3 4 5 6 7 8 9
	RECOMMENDATIONS Bicycle Lockers	13
2)	ANDSCAPE	
	DESIGN STANDARDS Species List	16
	RECOMMENDATIONS Drinking Fountains	24
3)	MONUMENTATION	
	DESIGN STANDARDS Retail and Office Signage	26 27
	RECOMMENDATIONS Wayfinding Signs Monumentation Other Signage Options	30

4) ATTACHMENT A - Sample Products

Photographs and drawings are shown of the particular items that should be specified in each new development proposal within the district. These images are shown as specific guides on style, finish, and material types. However, no particular manufacturers have been identified (except where an existing city standard exists, and any combination of comparable equals would be accepted. Attachment A consists of product cut-sheets from specific manufacturers that could be used for comparison.

Design Standards

TREE GRATES

TREE GRATE SPECIFICATIONS

Material: Cast Iron

Finish:

Raw cast iron grey

Size:

5' SQ

Placement/Spacing: 30' - 50' spacing on center

Application: Optional on Principal streets, and other approved locations



TREE GUARDS

TREE GUARD SPECIFICATIONS

Materials:

Fabricated steel construction

Black high polish Powdercoat


Size:

16" diameter

5' height

Placement/Spacing: 30' - 50' spacing on center

Application:Optional on Principal streets, and other approved locations



TRASH/RECYCLING RECEPTACLES



Recycle Lid For side-by-side receptacles

TRASH RECEPTACLE SPECIFICATIONS

Materials:

Fabricated steel construction

Finish:

Black high polish Powdercoat

Size:

36" diameter 48" height

Placement/Spacing: Minimum of 2 per block face, unless otherwise approved by the City

Application:

All Principal streets, and other approved locations



BOLLARDS



BOLLARD SPECIFICATIONS

Materials:

Cast steel

Finish:

Black high gloss Powdercoat.

Size:

4" diameter

36" height

Mounting Options: Cast-in, Bolt-down (surface mount), or Removable.

Placement/Spacing: Minimum 4' spacing, Maximum 6' spacing

Application:

All Principal street intersections, and other approved locations

BENCHES

BENCH SPECIFICATIONS

Materials:

Ductile cast iron end frames, steel straps

Finish: Black high gloss Powdercoat

Size: 5/16" x 1 ½" wide straps 6' length

Placement/Spacing: Minimum of 3 per block face

Application: All Principal streets, and other approved locations



PLANTERS

PLANTER SPECIFICATIONS

Materials:

Concrete

Finish:

Natural concrete color and texture. No stamping or staining

Size:

Planter Option A 6" high, 6" depth Planter length and width will vary

Planter Option B


18" high, 10" depth Planter length and width will vary

Placement/Spacing:


Option in place of tree grate
Planter Option A - 30' - 50' spacing on center
Planter Option B - Maximum of 2 per block face

Application:

All Principal streets, and other approved locations



LIGHTING FIXTURES



LIGHTING SPECIFICATIONS

Manufacturer:

Holophane

Model Series:

Utility Washington Postlite Luminare (WAU-product nubmer) North Yorkshire Pole (NY13/20-CIS/BK)

Materials

Cast iron & steel pole Glass and cast aluminum luminare

Finish:

Black trim on luminare Black pole finish

Pole Size:

15' pole height 20" diameter base

Accessories/Notes:

Banner arms (BA24H/1/BO) Single lamp, rather than the double


Placement/Spacing:

Principal Street - 30' - 50' spacing on center stagger with landscaping

Non-principal Streets - spacing to meet minimum required lighting levels

Application:

All streets, and other approved locations



BICYCLE RACKS

BICYCLE RACK SPECIFICATIONS

Materials:

Steel tubing

Finish:

Black semi-gloss Powdercoat

1-1/2" diameter tubing, 27 1/2" wide, 32" high.


Placement/Spacing:

Install in groups of three minimum, seven maximum. Minimum one group per block face

Application: All Principal streets, and other approved locations



PAVING PATTERNS & PAVERS



PAVING ACCENT SPECFICATIONS

Materials:

Varies. May be brick, stained concrete, or other paving material as long as the surface and seams are smooth as to not impede

Applications:

Approved locations. Paving accents are to be used to articulate building entries, pedestrian crosswalks, plazas, or

Patterns:

Paving accents should follow a 2' 6" grid, or other 2' 6" modular pattern variation.

PAVING PATTERN SPECIFICATIONS

Materials:


Concrete

Finish:

Natural concrete, may stain. No stamping.


Scoring Patterns:

2' 6" grid, or as shown in detail below



Recommendations

BICYCLE LOCKERS



BICYCLE LOCKER SPECIFICATIONS

Materials:Solid steel top with perforated steel walls


Finish: Black high gloss Powdercoat.

Size:

47" height 76"' length 39"' width

Additional Notes:

2 bicycles per modular unit Stackable Padlocking handles



INFORMATIONAL KIOSKS

KIOSK SPECIFICATIONS

Materials:

Steel or aluminum construction

Finish:


Black high gloss Powdercoat.

Size:

Variable

Notes:

Kiosks may be a custom design and do not need to match the photograph to the left. However, kiosks must be of a similar level of quality.



CLOCK

CLOCK SPECIFICATIONS

Materials:

Cast iron post

Finish: Black high gloss Powdercoat.

Clocks may be a custom design and do not need to match the photograph and drawing to the left. However, clocks must be of a similar level of quality.



Design Standards

SPECIES LIST

Street Tree List:

East - West Streets:

Pacific Sunset Maple and Red Spire Pear

North - South Streets:

Zelkova and Aristocrat Pear

Planted Medians:

London Plane, Red Maple and Burr Oak

Open Spaces along Couplet Streets:

Bur Oak and Red Maple

Additional Medium Shade Trees-

for use in public and private open spaces::

Canada Red Choke Cherry

Tatarian Maple

Flame Maple

Western Redbud

Amur Maple

Forest Pansy Eastern Redbud

Thornless Honeylocust

Red Barron Crabapple

Chanticleer Pear

Planting/Spacing:

30'- 50' spacing on all street trees

Plant Schedule:

Deciduous Shrubs		
Ruby Carousel Barberry	2 Gal.	3 ft spacing
Green Velvet Boxwood	2 Gal.	3 ft spacing
Ivory Halo Dogwood	2 Gal.	4 ft spacing
Hancock Coralberry	2 Gal.	4 ft spacing

Evergreen Shrubs


ronground annual		
Trailing Euonymus	1 Gal	3 ft spacing
Moonshadow Euonymus	1 Gal	3 ft spacing
Otto Luyken Laurel	3 Gal	4 ft spacing
Dwarf Periwinkle	flat	12" spacing

Ornamental Grasses

Karl Foerster Feather Grass	1 Gal	3 ft spacing
Varigated Maiden Grass	1 Gal	5 ft spacing
Fountain Grass	1 Gal	4 ft spacing


Perennials

Woodside Ruby Daylilly 1 Gal 2.5 ft spacing



Power should be installed in tree grates following the above detail.

Street TreesEast - West Streets:




Pacific Sunset Maple

Street TreesNorth - South Streets:



Zelkova



Red Spire Pear



Aristocrat Pear

Street TreesPlanted Medians:



London Plane



Burr Oak



Red Maple

Additional Medium Sade Trees

For use in public and private open spaces



Amur Maple



Imperial Honeylocust



Tatarian Maple




Chanticleer Pear

Additional Medium Sade Trees

For use in public and private open spaces



Canada Red Choke Cherry





Red Barron Crabapple



Forest Pansy Eastern Redbud

Additional Medium Sade Trees

For use in public and private open spaces



Flame Maple

Deciduous Shrubs



Green Velvet Boxwood



Ivory Halo Dogwood



Ruby Carousel Barberry



Hancock Coralberry

Evergreen Shrubs



Moonshadow Euonymus



Dwarf Periwinkle

Ornamental Grasses



Variegated Maiden Grass



Karl Foerster Feather Grass



Fountain Grass



Otto Luyken Laurel



Trailing Euonymus

Perennials



Woodside Ruby Daylilly

Recommendations

DRINKING FOUNTAINS

DRINKING FOUNTAIN SPECIFICATIONS

Materials:

Cast aluminum or steel base, bronze basin


Black high gloss Powdercoat.

Application: Park space, and other approved locations



Design Standards

PEDESTRIAN ORIENTED RETAIL & OFFICE SIGNAGE




RETAIL & OFFICE SIGNAGE RECOMMENDATIONS

Notes:

Retail and office signage in the Murray Fireclay TOD/Redevelopment Area should be pedestrian oriented. The City should consider modifying the City's sign and TOD ordinances to allow for blade or sidewalk monument signs in this district.







STREET SIGNAGE

SIGNAGE SPECIFICATIONS

Finish:

Black trim on signs Black pole finish


Notes:

Signs fabricated at Murray City's Sign Shop.

Street sign graphics should be developed as part of a district branding process.

Street Naming Conventions:

All East-West streets should be called "Avenues". All North-south Streets should be called "Lanes" or "Drives," with the exceptions of Boulevards and Promenades.



Recommendations

WAYFINDING SIGNAGE

SIGNAGE SPECIFICATIONS

Finish:

Black trim on signs Black pole finish

Notes:

Signs fabricated at Murray City's Sign Shop.

Wayfinding signage and all sign graphics should be developed as part of a district branding process.

The photograph below is an example of wayfinding signage, the actual signs selected for the Fireclay TOD do not need to match this example exactly, but should be of a similar level of quality and appearance.



DISTRICT MONUMENTATION




MONUMENTATION SPECIFICATIONS


Notes:

Murray Fireclay TOD/Redevelopment Area monumentation will be developed as part of a district branding process. However, monumentation features may include hanging blade signs, stone monuments, or other types of signs. Below are a few examples which









OTHER SIGNAGE OPTIONS

